

TacStud

Tactile Indicator
Polyurethane Warning Tactile Studs



The TacStud Polyurethane Warning Tactile Studs are made from hard wearing thermo polyurethane material, with added UV stabilizers and have been designed for safety and dignity, while providing superior durability in all substrates.

The retrofit design fixed by engineered stems for friction fitting into most substrates has meant the TacStud has proven its design and specifications in many harsh conditions and high foot traffic environments.

Standards

The TacStud Polyurethane Warning Tactile Studs comply and exceed the requirements of:

AS/NZS 1428.4.1:2009

NZTA RTS14

NZS 4121:2001

AS/NZS 3661.1.1993

AS/NZS 4586:2004

Types & Applications

- THISS25 – 25mm stem x 8mm diameter Star Shaft friction fitted into Concrete, Timber, Pavers, Carpet, Vinyl Substrates
- THIS12 – 12mm stem x 8mm diameter Star Shaft friction fitted with epoxy (Hilti RE500) into Tiles, Stone Paver Substrates
- THIFS25 – 25mm stem x 10mm diameter Fin Shaft friction fitted into Asphalt, Chip Seal Substrates

Features

- Excellent Anti-Slip Rating
- Easy retro fit install
- UV stable thermos polyurethane
- Superb abrasion qualities

Tactile Colours: Yellow, Black, Grey, White, Green, Blue, Terracotta, Beige, Charcoal



Other colours available on request.

