



CA290

Sealant/Adhesive Instant Grab Construction Adhesive

Adhesive (CA290) is a high quality instant grip polymer adhesive designed for the building and construction industry. The product is odourless and silicone, solvent, phthalate, PVC and isocyanide free.

Features

- Instant grab characteristics
- High durability with good weathering and water resistance
- Ready for immediate use in 290ml cartridge
- Works on almost all surfaces
- Excellent adhesion on almost all types of surfaces
- High abrasion and tear strength
- UV, water (salt & fresh) and weather resistant
- Temperature resistance is -40°C to 100°C

Application

Can be applied to almost any surface. Always test prior to application.

Not recommended for application on PE, PP, PC, PMMA, PTFE, Neoprene, Teflon, bituminous surfaces, or for continual water immersion and expansion joints. Great for internal and external applications for building and industry situations.

It is advised that CA290 is applied with a heavy-duty applicator gun. CA290 must be applied in volumes relating to material surface and weight of object, through large V shaped nozzles (as supplied). Apply in triangular beads, approximately 20 mm apart, then press the 2 materials together firmly so that the thickness is no thinner than 3mm. CA290 should not be applied in dots. If applied correctly no support is required during curing.

Specifications


Applications:

Colours: N/A


For best performance




Use V-Shaped Nozzle (supplied) to allow a good uniform flow



Use Caulking Gun with at least a 18:1 ratio



Apply in straight lines with the V-shaped groove facing up, for triangular beads



For vertical applications, apply beads vertically

Application Temperature

Min: +5°C

Max: +40°C

